

2A15.PP



Liner con coating in polipropilene (PP) destinato al risanamento di ogni tipo di condotte a gravità, comprese ghisa, ghisa sferoidale, acciaio, PVC e amianto-cemento.

- sistema di rivestimento monostrato o multistrato
- riabilitazione di condotte a gravità
- Installazione a inversione o trascinamento
- Utilizzabile con resina poliestere, vinilestere e epossidica

Liner with polypropylene (PP) coating for the restoration of all types of gravity ducts, including cast iron, ductile iron, steel, PVC and asbestos-cement.

- *Single layer or multilayer coating system*
- *Restoration of gravity ducts*
- *Reverse or drag installation*
- *It can be used with polyester, vinylester and epoxy resin*

	DATI TECNICI GENERALI	GENERAL TECHNICAL DATA
Diametri (mm) <i>Diameter (mm)</i>	DN 150 - DN 2000	
Tipologia di coating <i>Type of coating</i>	Polipropilene [PP]	<i>Polypropylen [PP]</i>
Peso superficiale coating <i>Superficial weight coating</i>	450 [g/m ²] - 1000 [g/m ²]	
Spessore minimo coating <i>Minimum coating thickness</i>	400 - 450µm	
Polimerizzazione <i>Curing method</i>	Acqua calda o vapore	<i>Hot water or steam</i>

